



Wiser With Energy

Technical Data Sheet

V180323

FACADE5finish



Liquisol bvba Noorderlaan 147 B9,2030 Antwerp, Belgium
VAT: BE0648.867.048 tel: 00 32 32 56 01 72 verf@liquisol.com
In case of online purchase conflict: <http://ec.europa.eu/consumers/odr>



FACADE5finish is a solar reflective waterborn acryl coating to be applied on walls an roofs. Available in nearly every RAL colour.



Visit the “how to install” movie.
You will need to clean the surface with s00p RWC.



For convenience, FACADE5finish is packaged in a plastic pouch with a screwtop. It must be stored between 4°C and 30° C, and keep out of direct sunlight. 4EVERblue must used within 6 months of opening or 2 years after purchase. EAN code 5 liter = 5425027113154

The usage per liter is 6 m² or 64 sq²
5 liter = 30 m² = 323 sq²



You should wear protective clothing when using this product. When spraying 4EVERblue, you should wear a mask with a combination filter of at least A/P2. Gloves and overalls should also be worn. The EU limit for 3SEASONSblue is (Klasse A/i) : 2010: 140g/ litre. VOC level is 5g/ litre. Read the MSDS for more information.



Authorized Liquisol Applicator ALA may give 5 years factory warranty.
At at correct installation, a lifetime of 8 to 10 year can be expected.



Use 8 mm paintroller or airmix with opening 018 – 021, pressure = 80 - 150 bar (Graco Airmix 595.)

apply at min 10°C , relative humidity = max 80% Surface temperature = min 10°C- max 35°C. Do not apply in full sunlight or at high risk at rain or damp; dry = 18h at 20°C and 65% RH (relative humidity)



Black RAL 7021: Near Infrared Reflectance = 42%, Solar Reflectance = 26%
Blue RAL 5015: Near Infrared Reflectance = 69%, Solar Reflectance = 47%
Beige RAL 1013: Near Infrared Reflectance = 86%, Solar Reflectance = 77%